



WATER TREATMENT ESSENTIALS

Keep Your Water Treatment Facilities Running Efficiently

Loctite® QuickStix™ Threadlocker Variety Kit

The most popular Loctite threadlockers for use in vibrating assemblies are available in a convenient kit. Comes in stick form for easy application.

- No dripping.
- Works on all metals
- 268 (Red) is high-strength adhesive designed to permanently lock assemblies
- 248 (Blue) provides a medium strength bond to prevent loosening; can be removed by hand tools
- 7088 Primer Paste speeds the cure rate of the adhesives

Kit Includes:

- 1 Loctite Quickstix 268 Red Threadlocker – 1143635
- 1 Loctite Quickstix 248 Blue Threadlocker – 1143641
- 1 Loctite Quickstix 7088 Primer – 1143596

Item No.
1600259



Drummond Metalize with Steel Scratch Brush

Converts rust to a solid polymer to protect surface from future rust, moisture and contamination, all in one easy step. Just remove grease, dirt, and loose, flaking rust with steel brush. Sandblasting is not required.

- Cures to a tough black finish coat which can be painted over
- Temperature range: Up to 250°F (121°C) when cured
- Brush to remove rust has wooden handle with 10" x 1-1/8" block size
- Pkg. Qty. 1

Kit Includes:

- 3 Metalize Rust Converter. Net Wt. 10.25 oz. – DA7490
- 1 Steel Brush – 83906

Item No.
1536654



Rotanium Blue Grease HT Waterproof, Multi-Purpose Grease

High-performance, calcium-sulfonate based grease for general industrial maintenance applications. Extremely resistant to water washout, will not break down under heavy load applications.

- Applications include mechanical hoists, conveyor systems, anti-friction bearings, exposed gears, and drives
- Wide temperature range: 0°F to 500°F
- Pkg. Qty. 1
- Net wt. 11.5 oz.

Item No.
1599238





WATER TREATMENT ESSENTIALS

Keep Your Water Treatment Facilities Running Efficiently


Patch 'N Bond™ AquaStik Epoxy Repair Compound Stick

Easy-to use, two-part single stick ensures a correct component mix every time. Simply cut off required amount, knead to a uniform putty-like consistency, and apply. Cures quickly even under water.

- No drips or runs
- Cure Time: 3 to 20 minutes
- Can be drilled, sawed, carved, sanded, stained, painted, or filed within an hour
- Resists most chemicals
- Pkg. Qty. 1
- Size. 4 oz.

Item No. Aquastick Bronze
P45335

Item No. SteelStik White
55374



LU 103 Rust Breaker Heavy-Duty Rust Penetrant

Fast-acting petroleum-based product quickly loosens rust while penetrating grease and dirt. A transparent, non-staining oil, its light film displaces moisture and acts as a corrosion preventative. Jet stream sprays up to two feet for safe, accurate application. Pleasant vanilla scent. It is a one-coat rust and corrosion preventive compound.

- High dielectric strength: 47,400V
- Temperature range: -20°F to +550°F (-28°C to +287°C)
- NSF H2
- Pkg. Qty. 12
- 16 oz. can size; 10 oz. net wt.

Item No.
1143332



Lubri-Temp Multipurpose Anti-Seize

Provides a long-lasting protective coating in highly corrosive and hot environments to prevent metal-to-metal seizing, galling, and sticking in stainless steel and petrochemical applications

- Special blend of synthetic oil and solids ensures resistance to decomposition and oxidation
- Excellent water washout resistance.
- Not recommended for high-speed, close tolerance bearing applications.

Item No. 16 oz. Brush Top Can
19921

Item No. 5 lb. Plastic Can
19923

Item No. 13 oz. Aerosol
19920

