



The TORRENT 500 and TORRENT 700 Parts Washer

High Pressure Aqueous Parts Washers that solve the problem of traditional parts washing machines.

The Torrent Rental Program includes the following:

- Full run through and training of mechanics
- Needed supplies for use (gloves, filters, soap, etc)
- Any other required maintenance parts & repairs



TORRENT 500

115 ETL PARTS WASHER
Item No. PM99974000

PRICE: \$8,990.00



Check out the
Torrent 500 in action



TORRENT 700

115 ETL PARTS WASHER
Item No. PM99977000

PRICE: \$9,998.00



More information on
the Torrent 700

TORRENT 500

RENTAL PRICE:

Monthly Rate

1 Year - \$375.00

2 Year - \$345.00

3 Year - \$325.00

4 Year - \$300.00

TORRENT 700

RENTAL PRICE:

Monthly Rate

1 Year - \$500.00

2 Year - \$460.00

3 Year - \$425.00

4 Year - \$390.00

Contact

Kevin Landis

**Torrent National Sales
Manager**

Phone: 740-361-1116

Email: [Kevin.Landis@
LawsonProducts.com](mailto:Kevin.Landis@LawsonProducts.com)

Doug Antilla

**Strategic Account
Manager**

Phone: 913-671-0563

Email: [Doug.Antilla@
LawsonProducts.com](mailto:Doug.Antilla@LawsonProducts.com)



MEGA Chemicals

Wear-Flex™ Quick-Mix™ 2500

All-Purpose Flexible Rapid Repair Compound

A 2-part urethane repair compound that forms a flexible bond on a variety of materials. Perfect for applications that involve vibration or expansion/contraction movement.

- Forms a flexible bond that withstands chemicals, grease, oil, and water
- Remains flexible at low temperatures
- Tensile Strength: 1,300 PSI
- Temperature Range: -40°F to 250°F (-40°C to 121°C)
- Working time: 1 - 2 minutes
- Functional cure: 4 hours
- Ideal for repairing damaged forklift and off-road tires and repairing cracks and joints in concrete

1634872 - 400ml, Non-Sage Adhesive



Mega-Tech Brushable Ceramic Kit

A brushable epoxy coating specially blended with abrasion resistant ceramic fillers. Provides a durable barrier to protect surfaces subjected to wear and abrasion. Easily applied by brush to most surfaces. Waterproof and resistant to most chemicals and solvents. A thick and creamy epoxy coating that allows for vertical and overhead application.

- Ultra-pure silicon-based ceramic particles
- Smooth, high-gloss surface
- Reduces cavitation and material hang up and increases flow efficiency
- Creates greater strength
- Applies at 6–10 mils.
- Superior protection from rust or corrosion
- Cure Time: 4-6 hours

1637120 - 2 lbs, base and activator



Mega Stick™ Instant Steel Patching Compound

- Ideal for emergency repairs even on damp surfaces
- Cures in 15 minutes for fast repairs
- Easy to apply—no measuring, no mess; just cut off desired amount, knead and apply
- Can be drilled, filed, sanded, tapped and painted
- Chemical and corrosion resistant
- Safe for use in potable water systems—conforms to NSF Standard 61
- Temperature range: -40°F to +250°F (-40°C to +121°C)

EG57020000 - 4oz. Tube



Mega-Crete Slurry II

Medium-cure concrete and masonry resurface and repair compound.

- 4X stronger than concrete
- Excellent for repairing spalled and damaged concrete
- Cure hard in 2.5 hours for vehicle traffic
- Easy to mix; 2 to 1 ratio
- Can be applied to cold floors down to 35°F/2°C
- Low odor
- Resistant to fuels and lubricants
- Bonds to concrete, masonry, metal/rebar, and wood
- Color: Gray
- Working time: 30 minutes
- Functional cure time: 3 hours

1635345 - 20 lbs.

